

# Fiesta Awning Annexe Instructions



Fiesta with optional annexe

Thank you for purchasing your Fiesta annexe. Please read these instructions carefully before attempting to set up your annexe and retain for future reference. If used properly, your annexe should give you years of trouble free use. We recommend that your awning and annexe is insured against accidental and storm damage as this is not covered by the warranty. Awnings contain a high proportion of synthetic materials and under certain conditions will be affected by condensation inside the awning. This should not be confused with leaking and condensation can be improved by ensuring adequate ventilation.

We recommend a trial run before using your awning and annexe for the first time. This will allow you to familiarise yourself with the awning, its set up and any limitations the awning may have for your particular use. Please also check your caravan awning rail to ensure that it is not damaged or has any sharp edges that could damage your awning.

## PARTS LIST

Annexe flysheet	1
Fibreglass pole	1
Peg bag	1
Carry bag	1

If any parts are missing please contact your supplying retailer immediately.

Kampa UK Limited  
Witham  
CM8 EU



## SET UP

Unzip one of the side panels from your Fiesta awning. The annexe can fit either side. Zip the annexe onto the awning. To avoid leakage, adjust the zip runners so that they are positioned close to the ground. Slot the fibreglass pole together, making sure that each section is fully inserted into the adjoining ferrule. Push the pole through the black pole sleeve on the annexe. Put each end of the pole on the pin at the bottom of the awning. The pin is on an adjustable webbing strap. The strap can be released to make it easier to insert the pin into the bottom of the pole. Always retighten the straps to ensure that the awning is tensioned correctly. Attach the clips on the annexe to the pole.



1. Zip the annexe into the awning
2. Push the pole through the sleeve
3. Place the pin in the bottom of the pole and retighten strap



Peg the annexe starting with the four corners, pegging the corners closest to the awning first and then the outermost corners. Ensure the annexe is sitting square and adjust if necessary. Peg the intermediate pegging points and then guy out using the pre-attached guylines.

Take the inner tent inside the annexe. Peg the groundsheet squarely within the annexe ensuring that the doorway faces out. Attach the annexe walls to the inner tent by pushing the toggles, on the inner tent, through the D-rings on the annexe walls. If necessary re-adjust the pegged groundsheet.

## SEAMS

The main seams of this annexe have been factory taped to help prevent leakage. Depending upon your expectations, it may be necessary to treat the remaining seams with a seam sealant. Seam sealant should also be applied to areas where the taping is damaged or has peeled away through wear and tear. It can also be applied to areas where a leak may have developed. Seam sealant is available through your dealer. We recommend McNett SeamSure.

## UV DEGRADATION

Awning fabrics can be weakened by prolonged exposure to sunlight. Under normal holiday use your awning will give long service but use for extended periods in strong sunlight will soon cause deterioration. In those cases it would be wise to use a site as shaded as possible. UV degradation is not covered under the warranty. The warranty does not cover awnings used on permanent sites, displays or for commercial purposes.

## CONDENSATION

Awnings contain a high proportion of synthetic materials and under certain conditions will be affected by condensation inside the awning. This should not be confused with leaking and condensation can be improved by ensuring adequate ventilation. Condensation and its effects are not covered under the warranty.

## DISMANTLING

Reverse the set up procedure. Ensure that all parts are clean before packing in the carry bag. If the annexe is wet or damp, dry fully as soon as possible.